



Description

TS-9175 is wireless transfer module combined with video signal and control signal, which can match with wireless touch screen TS-9169B and can realize picture in picture play function by receiving CVBS standard video system and then convert to wireless video signal send to wireless touch screen.

Features

- * One BNC video input port, one RCA video input port, support CVBS standard input, PAL/NTSC auto check.
- * H.264 Video coding, support 1 channel D1@25 frame+1 channel CIF@25 frame dual code stream. AVI format. Support adjustable code stream: 0.1M~2Mbps, support frame rate 1-30 frame adjustable.
- * Standard RJ45 internet port, support 10/100m auto adaptive.
- * Standard central control internet port, can connect with all ITC programmable center control directly.
- * ID Choosing: Device has ID identification, easy for system cascade extension.
- * 150Mbps Wireless Speed can reach 150Mbps:
 1. Wireless Standard: IEEE 802.11n: IEEE 802.11g, IEEE 802.11b.
 2. Wire Standard: IEEE 802.3, IEEE 802.3u.
 3. Frequency Range: 2.4-2.4835G.
 4. Transmitting Power: 12-15DBM.
 5. Wireless Security: WPA-PSK/WPA2-PSK, WPA/WPA2 Security system.
- * Wireless WIFI effective range: 70 M in open field.

Specifications

Model	TS-9175
Power	DC12V
Working Temperature	-10~40
Power Consumption	3W
Dimension(mm)	135(L)×110(W)×33(H)
Weight	0.5Kg