



17R Moving Head Beam Light

TL-YTA1-01



Technical Parameters

Model	TL-YTA1-01
Power Supply	AC110V-240V 50/60Hz 500VA
Ballast	Electronic Ballast
Lamp	17R/YODN MSD 350
Color Temperature	7800K
Average Life Expectancy	2000H
Optical	High-precision glass optical lens (6-layer coating), multi-level optical lens group electronic focusing, linear amplification
Beam Angle	0-2 degrees of parallel light, 8° angle of atomizing light
Dimming	0-100% linear adjustment
Color Wheel	11 color pieces + 1 blank, two-way rainbow effect, adjustable speed, arbitrary positioning function
Fixed Pattern Plate	12 fixed pattern pieces + 1 blank, with pattern jitter, one-way flow, adjustable speed, arbitrary positioning function
Effect Pattern Plate	None
Rotating Pattern Plate	None
Prism	1 prism mirror can be rotated in both directions, 16 prism effect, 8 prism effect, 2 prisms can be superimposed
Strobe	Two-chip strobe 0.5-20 times / s, with synchronous, asynchronous, random strobe mode, adjustable speed
Atomization	None
Scan Range	X-axis 540°/2.5 S, Y-axis 240°/1.5 S, resolution: 8Bit/16Bit
Display Interface	Adopt wide LCD screen with English display interface
Motor	The XY axis adopts three-phase motor, 16Bit drive
Control Method	DMX512 (DMX wireless) optional
Channel	13/16 channel
Lighting Materials	High temperature plastic + molded alloy material
Protection And Other Energy	IP 55
Lamp Size	440X410X620 mm
Packing Size	520X490X675mm
Gross Weight / Net Weight	29KG/25.2KG