

Technical Parameters

Model	TL-XGB1-01
Rated Voltage	AC110V~240V, 50~60Hz 200VA
Light Source	18×10W LED(4IN1)/Average life 50000H
Color Yemperature Correction	3200K~7200K Linear adjustment
Lens Sngle	25°
Illumination Dngle	adjustable angle
Strobe	Independent electronic strobe 1-25Hz, random strobe, pulse strobe, synchronous and asynchronous
	strobe, monochrome, mixed color temperature strobe
Color Mixing	RGBW (red, green, blue, white) linear color mixing, 16.7 million colors (0-100% saturation
<u> </u>	adjustable), built-in megafunction
Electronic Dimming	Electronic dimming: 0-100% independent electronic linear dimming, camera video is true without
ÿ	flicker, master-slave auto-synchronization function, console normally controls self-propelled
	permanent synchronization.
LCD Menu	call various scenes, built-in programs can directly call execution
Control Mode	multiple voice control, DMX512, built-in program self-propelled, master-slave online mode,Pixel
	control
Channel	8/14/26/38/74 channel (optional for five channel modes)
Lamp Connection	three-core signal line IN/OUT power line IN/OUT
Features	cast aluminum housing, high luminous efficiency, uniform light mixing, stable performance, With one
	input and one output hand in hand 1 meter power and signal line, 1024-level ultra-high grayscale
	dimming is more soft
Protection Grade	electrical class II, fire protection V-1, protection IP65
Working Environment	-20°C~40°C
Product Size	1060*105*165mm
Net Weight/ Gross Weight	7.1 kg/8.5 kg