



Ultra-thin Speaker

T-4535C



Application

PA system in airports, cars, railways and subway stations; Internal broadcasting in ships and warships; PA system and emergency broadcasting in schools, shopping malls, hotels, and institutions; Emergency broadcasting in public places such as parks and squares.

Features

- * Ultra-thin shape, thickness 32mm; Aluminum alloy structure, sturdy structure, corrosion resistance, durability.
- * It adopts imported polymer multilayer honeycomb diaphragm, featuring low Young's modulus, light weight, high bending resistance and moderate damping.

- * Built-in 4 drivers adopts NdFeB strong magnetic circuit; 2 20mm silk diaphragm tweeters.
- * 360 degree sound(front and rear), plane wave transmission, comfortable human voice, and long transmission distance.
- * Wide frequency response range, 150Hz-18KHz plane sound.
- * Ultra-thin (32mm) housing, high-strength aluminum alloy material, fine anodized sand grains on the surface, elegant appearance.
- * Support multi-point installation, horizontal and vertical installation.
- * Anti-mildew, moisture and salt spray.

Specifications

Model	T-4535C
Rated power	50W
Max sensitivity	104dB
Sensitivity	88dB ±3dB
Voltage	100V
Frequency response	150Hz -18KHz
Diaphragm area	156mm×314mm×2
Driver	4 woofer drivers; 2 tweeter drivers.
Dimension	450×350×32mm
Weight	2.15Kg