



Moving Head Light

TL-SL186



Feature

- * Color mixing system: CMY+CTO color mixing system, stepless changing color.
- * Color wheel: 6 colors + 1 white light.
- * Fixed gobo wheel: 9 gobos + 1 white light, adjustable speed, flexible positioning function.
- * Rotating gobo wheel: 7 replaceable gobos + white light, bidirectional rotation and positioning.
- * Effect pattern wheel: Fire pattern/Water pattern, bidirectional rotation.
- * Focusing: Linearly adjustable focusing/infrared auto-focusing function.
- * Prism: Quadrangular prism, bidirectional rotation and positioning.
- * Zoom in: 11× zoom 5-55°.
- * Atomization: An atomization effect.
- * Scanning range: X-axis 540~630°/2.7 S, Y-axis 270°/1.5 S, accurate scanning and positioning.
- * Display interface: A wide-screen 2.4-inch LCD interface in Chinese and English, with rechargeable battery; you can enter the menu to set the address code and perform other settings without powering it on; the menu is hierarchically structured and has a friendly graphical interface.
- * Intelligent heat dissipation: Using wind direction drainage and temperature intelligent monitoring technology, built-in NTC temperature control function, when it is overheated, the output power of the LED is intelligently reduced.

Specification

| | |
|----------------------|--|
| Model | TL-SL186 |
| Input voltage | AC110V-240V 50/60Hz, 800W |
| LED light source | 600W |
| Average lifespan | 50000H |
| Color temperature | 6500K |
| Beam angle | 5~55° |
| Control mode | DMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface (DMX wireless function optional) |
| Channel | 26/15CH |
| Fixture material | High temperature resistant plastic + molded alloy material |
| Protection class | Ip30 |
| Fixture size (L×W×H) | 427×276×765mm |
| Package size (L×W×H) | 515×365×855mm |
| Gross weight | 37.2kg |
| Net weight | 33.2kg |