



Feature

- * Composed of a 8-inch subwoofer unit and a 1-inch dome tweeter.
- * Designed with ABS+PC injection molding, suitable for all-weather use.
- * Equipped with an aluminum mesh grille and an acoustic sound-permeable sponge inside to prevent dust and water droplets from damaging the speaker unit.
- * Precise two-way crossover design is adopted to optimize the frequency response and the mid-range expressiveness of the vocal part.
- * With constant resistance and constant voltage selection function. With a U-shaped bracket, it is convenient for engineering installation.
- * Suitable for indoor and outdoor fixed installation; applied to BGM broadcasting applications in theme parks, scenic spots and other cultural tourism sound reinforcement scenarios.

Specification

Model	TW-778K
Speaker type	Plastic wall mounted speaker
Rated power (100V)	10W/20W/40W/80W/constant resistance 8Ω, 80W
Rated power (70V)	10W/20W/40W/80W constant resistance 8Ω, 80W
Nominal impedance	1000Ω/500Ω/250Ω/125Ω/62Ω constant resistance 8Ω
Frequency range (-10dB)	65Hz-20kHz
Sensitivity (1M/1W)	93dB±3dB
Maximum SPL	115dB
Coverage angle (-6dB)	110°(H)×90°(V)
Subwoofer	8-inch subwoofer×1
Tweeter	1-inch tweeter×1
Net weight	6.6kg
Dimension (H×W×D)	406×250×251mm